



Safety Data Sheet

according to OSHA HCS 2012, 1272/2008/EC (CLP), and UN GHS

Print Date: 6/11/2015

Heavy Traffic Carpet Foam

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Heavy Traffic Carpet Foam (1135E, 69M5E, 69M5F, 69M5K, 4090825, 4091829 and 38A5 Series)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Carpet or Upholstery cleaner

1.3. Details of the supplier of the substance or mixture

BISSELL Homecare, Inc.

PO Box 1888, Grand Rapids, MI 49501

(616) 453- 4451, www.BISSELL.com

BISSELL Australia Pty Ltd

42 Rocco Drive, Scoresby VIC Australia 3179

1300 247 735, www.BISSELL.com.au

1.4. Emergency telephone number

Prosar (Medical) +1 866-303-6951

Chemtrec (US) +1 800-424-9300 acct 2808

Chemtrec (Int'l) +1 703-527-3887

SECTION 2: Hazard identification

2.1. Classification of the mixture and 2.2. Label elements

Regulation	Classification	Pictogram	Signal word	Hazard/ Risk, Precaution/ Safety Statements
CLP (EC) No 1272/2008	Aerosol (Category 3), H229	None	Warning	H229, Pressurised container: May burst if heated P102, Keep out of reach of children. P210 Keep away from heat P251 Do not pierce or burn, even after use. P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
DPD (EC) No 1999/45	Pressurized container		Caution	S2, Keep out of reach of children. S15 Keep away from heat. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight and do not expose to temperatures exceeding 50 °C
HCS 2012, UN GHS	Aerosol (Category 3), H229	None	Warning	H229, Pressurized container: May burst if heated P102, Keep out of reach of children. P210 Keep away from heat P251 Do not pierce or burn, even after use. P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

2.3. Other hazards

None known



Safety Data Sheet

according to OSHA HCS 2012, 1272/2008/EC (CLP), and UN GHS

Print Date: 6/11/2015

Heavy Traffic Carpet Foam

Page 2 of 8

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Ingredient	Percent	Classification	EC Number/ CAS Number
Water	≥ 80	Not classified as hazardous	231-765-0 / 7722-84-1
Isobutane	< 5	(CLP) Flam. Gas 1; H220, Press. Gas; H280 (DPD) F +; R12 (GHS) Flam. Gas: 1; H220, Press. Gas; H280	200-857-2 / 75-28-5
Acrylate copolymer	≤ 2	Not classified as hazardous	Proprietary polymer
Sodium lauroylsarcosinate	≤ 2	(CLP) Skin Irrit. 2; H315 Eye Dam.1; H318 Acute Tox .2; H330 (DPD) T, R23, Xi; R38/41 (GHS) Skin Irrit. 2; H315 Eye Dam.1; H318 Acute Tox .2; H330	205-281-5 / 137-16-6
Propane	<1	(CLP) Flam. Gas 1; H220, Press. Gas; H280 (DPD) F +; R12 (GHS) Flam. Gas: 1; H220, Press. Gas; H280	200-827-9 / 74-98-6
Sulfonated Methylene-Bridged Phenolic Polymer	≤ 1	Not classified as hazardous	Proprietary polymer
Fragrance		(CLP) Eye Dam . 1; H318 (DPD) Xi; R41 (GHS) Eye Dam . 1; H318	
Alkyl polyglucoside	≤ 2	(CLP) Eye Irritant 1; H318 (DPD) Eye irritant; Xi ; R41 (GHS) Eye Irritant 1; H320	Proprietary polymer

For full text of the H-statements, R-phrases and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation: remove person to fresh air. If you are concerned, get medical advice.

Skin contact: wash with soap and water. If you are concerned, get medical advice.

Eye contact: flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed: rinse mouth, drink 1-2 glasses of water, do not induce vomiting. If you are concerned, get medical advice.

Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Use a fire fighting agent suitable for surrounding fire.

5.2. Special hazards arising from the substance or mixture

Pressurized container: May burst if heated



Safety Data Sheet

according to OSHA HCS 2012, 1272/2008/EC (CLP), and UN GHS

Print Date: 6/11/2015

Heavy Traffic Carpet Foam

Page 3 of 8

5.3. Advice for fire-fighters

Cool endangered packaging with water spray jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing inert material. Wash away residue with plenty of water. Dispose of contaminated material as waste according to Chapter 13.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50° C. Do not open by force or throw into fire even after use. See advice in chapter 8

7.2. Conditions for safe storage including any incompatibilities

Keep out of the reach of children. Store in closed original container in a well-ventilated place

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits, If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	PPM	mg/ m ³	Type	Remark
Hydrogen Peroxide 231-765-0 / 7722-84-1	1	1.4	Time weighted average; TWA	OSHA, NIOSH, UK HSE
Hydrogen Peroxide 231-765-0 / 7722-84-1	2	2.8	Short-term exposure limit; STEL	UK HSE
Isobutane 200-857-2 / 75-28-5	1000		Threshold limit value, TLV	OSHA
Propane 200-827-9 / 74-98-6	1000		Threshold limit value, TLV	OSHA, ACGIH

Biological limit values: No biological limit values exist for any of the components listed in Section 3

SECTION 8: Exposure controls/personal protection, continued

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray.

8.2.2. Personal protective equipment (PPE)



Safety Data Sheet

according to OSHA HCS 2012, 1272/2008/EC (CLP), and UN GHS

Print Date: 6/11/2015

Heavy Traffic Carpet Foam

Page 4 of 8

Eye/face protection
None required.
Skin/hand protection
None required
Respiratory protection
None required

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol white foam
Physical state	Foam
Odor	Pleasant
Odor Threshold	> 50 mg/ m ³
pH	9.0- 9.8
Flash Point	Not flammable
Melting Point/Range	Not applicable
Freezing point	0°C, 32°F
Boiling Point/Range	100 °C, 212°F
Autoignition Temperature	None
Flammability Limits in Air	Not flammable
Explosive properties	Not explosive

Oxidizing properties	Not oxidizing according to Regulation (CE) No 1272/2008
Vapor pressure	3.4- 4 hPa (Propellant)
Vapor density	No information available
Density	1.0 g/mL @ 20 °C
Partition coefficient	< 1 K _{ow}
Water solubility	Completely Soluble@20 °C
Viscosity	< 2 cP @ 20C
Evaporation rate	>1 (BuAc = 1)
Decomposition	> 100 °C

9.2. Other information

Volatile organic compounds (VOC) 4.9 g/l

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under normal conditions

10.2 Chemical stability

Stable

10.3 Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use

10.4 Conditions to avoid

Protect from sunlight. Keep away from heat, flames, other sources of ignition and direct sunlight. Keep container in a well-ventilated place

10.5 Incompatible materials

Reducing agents, strong acids, strong oxidizing agents

10.6 Hazardous decomposition products

Liable to produce overpressure in container. Refer to section 5.2 for hazardous decomposition products during combustion.



Safety Data Sheet

according to OSHA HCS 2012, 1272/2008/EC (CLP), and UN GHS

Print Date: 6/11/2015

Heavy Traffic Carpet Foam

Page 5 of 8

SECTION 11: Toxicological information

11.1 Information on Toxicological effects

Information given is based on product testing, and/or similar products, and/or components. The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from BISSELL assessments.

CMR effects: Not expected to be carcinogenic. Not considered a mutagenic hazard. No toxicity to reproduction

Acute oral toxicity: LD50:> 2000 - 5000 mg / kg Species: rat

Acute inhalation toxicity: LC50:> 20 mg / l

Acute dermal toxicity: LD50:> 2000 - 5000 mg / kg

Skin: Result: Not irritating.

Eye irritation: Result: Causes serious eye irritation.

Sensitization: Not expected to be a sensitizer

Toxicity Repeated dose: Not expected to be a hazard.

Target organ toxicity - repeated exposure: Not expected to be a hazard.

SECTION 12: Ecological information

12.1. Toxicity

Toxicity to fish: LC50:> 100-1000 mg / l, Exposure time: 96 h
Species: Fish

Toxicity to daphnia and other invertebrates that live in water:
EC50:> 100 to 1000 mg / l, exposure time: 48 h
Species: Daphnia magna, the value is estimated from tests on similar products.

Toxicity to algae: EC50:> 100 to 1000 mg / l, Exposure time: 72 h
Species: algae, the value is estimated from tests on similar products.

12.2. Persistence and degradability

Biodegradability: Result: According to the results of tests of biodegradability this product is considered as being readily biodegradable. > 60%, Method: OECD Guide- line 301 D - Ready Biodegradability: Closed Bottle Test

SECTION 12: Ecological information, continued

12.3. Bioaccumulative potential

Bioaccumulation: No accumulation expected

SECTION 12: Ecological information, continued

12.4. Mobility in soil

If the product enters soil, one or more constituents will or may be mobile and may contaminate groundwater.

SECTION 12: Ecological information, continued

12.5. Results of the PBT and vPvB assessment

Results of PBT assessment: This substance does not meet the Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available



Safety Data Sheet

according to OSHA HCS 2012, 1272/2008/EC (CLP), and UN GHS

Print Date: 6/11/2015

Heavy Traffic Carpet Foam

Page 6 of 8

SECTION 13: Disposal considerations

Waste from residues / unused products:

The concentrated contents or contaminated packaging should be disposed of by a certified handler or according to the site permit. Release of waste to sewers is discouraged. Small amounts may be diluted with plenty of water and washed away. Dispose of bigger amounts in accordance with Local Authority requirements The emptied packaging material is suitable for energy recovery or recycling in line with local legislation.

Empty packaging

Recommendation: Non contaminated packagings may be recycled.

Recommended cleansing agents: Water

SECTION 14: Transportation information

ADR: UN1950, AEROSOLS, 2.2, LTD QTY

IMDG: UN1950, AEROSOLS, 2.2, LTD QTY.

IATA: UN1950, AEROSOLS, 2.2, LTD QTY

RID: UN1950, AEROSOLS, 2.2, LTD QTY

DOT: UN1950, AEROSOLS, 2.2, LTD QTY

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Workplace Exposure Limits EH40. Commission Directive 2000/39/EC - indicative occupational exposure limit values

Regulation (EC) No 1272/2008 Regulation on the Classification, Labeling and Packaging of Substances and Mixtures (as amended).

Regulation (EC) No 1907/2006 Registration, Evaluation, Authorization and Restriction of Chemicals (as amended).

Authorisations (Title VII Regulation 1907/2006) No specific authorisations are noted for this product.

Restrictions (Title VIII Regulation 1907/2006) No specific restrictions of use are noted for this product.

Directive 1999/45/EC Dangerous Preparations Directive

Detergent Regulation 648/2004/EC

DIRECTIVE 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers

Water hazard classification (Germany): WGK 1 water pollutant (Self-assessment) slightly hazardous to water

Global inventory/ Notification status

CH INV: Y (positive listing) Compliance with the inventory

US.TSCA: Y (positive listing) All chemical substances in this product are either listed in TSCA inventory list or are in accordance with exceptions TSCA inventory list

DSL: Y (positive listing) All components of this product are on the Canadian DSL list.

AICS: Y (positive listing) Compliance with the inventory

NZIoC: N (Negative listing) Compliance with the inventory

ENCS: Y (positive listing) Compliance with the inventory

ISHL: Y (positive listing) Compliance with the inventory

KECI: Y (positive listing) Compliance with the inventory

PICCS: Y (positive listing) Compliance with the inventory

IECSC: Y (positive listing) Compliance with the inventory

For explanation of abbreviations, see chapter 16.

15.2. Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture



Safety Data Sheet

according to OSHA HCS 2012, 1272/2008/EC (CLP), and UN GHS

Print Date: 6/11/2015

Heavy Traffic Carpet Foam

Page 7 of 8

SECTION 16: Other information

The labeling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

According to directive No 67/548/EEC

- R5 Heating may cause an explosion
- R8 Contact with combustible material may cause fire
- R12 Extremely Flammable
- R20/22 Harmful by inhalation and if swallowed
- R22 Harmful if swallowed.
- R23 Toxic by inhalation
- R35 Causes severe burns.
- R36 Irritating to eyes.
- R37/38 Irritating to respiratory system and skin
- R38 Irritating to skin
- R41 Risk of serious damage to eyes
- R43 May cause sensitization by skin contact
- R50 Very toxic to aquatic organisms.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

According to regulation (EC) No 1272/2008

- H220 Extremely flammable gas
- H280 Contains gas under pressure; may explode if heated
- H271 May cause fire or explosion; strong oxidizer
- H290 May be corrosive to metals.
- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H318 Causes serious eye damage
- H319 Causes serious eye irritation.
- H320 Causes eye irritation
- H330 Fatal if inhaled
- H332 Harmful if inhaled
- H335 May cause respiratory irritation
- H411 Toxic to aquatic life with long lasting effects
- H412 Harmful to aquatic life with long lasting effects

Abbreviations

- CH INV Switzerland. New notified guest substances and preparations Declared
- US.TSCA United States TSCA Inventory
- DSL Canadian Domestic Substances List (DSL)
- AICS Australia Inventory of Chemical Substances (AICS)
- NZIoC New Zealand. Inventory of Chemical Substances
- ENCS Japan. ENCS - Existing and New Chemical Substances Inventory
- ISHL Japan. ISHL - Inventory of Chemical Substances (METI)
- KECI Korea. Korean Existing Chemicals Inventory (KECI)
- PICCS Philippines Inventory of Chemicals and Chemical Substances (PICCS)
- IECSC China Inventory of Existing Chemical Substances in China (IECSC)
- UK HSC : UK Health and Safety Commission
- ADR European Agreement concerning the International Carriage of Dangerous Goods by Road
- DOT Department of Transportation



Safety Data Sheet

according to OSHA HCS 2012, 1272/2008/EC (CLP), and UN GHS

Print Date: 6/11/2015

Heavy Traffic Carpet Foam

Page 8 of 8

SECTION 16: Other information, continued

Abbreviations, continued

IATA International Air Transport Association

IMDG International Maritime Code for Dangerous Goods

RID Regulation concerning the international carriage of dangerous goods by rail

The information herein is presented in good faith and believed to be accurate as of the effective date shown below. However, no warranty, expressed or implied, is given. Regulatory requirements are subject to change and may differ from one location to another. It is the buyer's responsibility to ensure that its activities comply with federal, state or Provincial, and local laws.

Effective Date: June 11, 2015

Supersedes: Not applicable, new issue

Prepared By: Don Mahaffy

BISSELL Homecare, Inc.

2345 Walker Ave NW

P.O. Box 1888

Grand Rapids, MI 49544 USA

Tel: +1 (616) 453-4451

Fax: +1 (616) 453-1383

<http://www.bissell.com/>